

Sub
a/

What is claimed is:

1. A method for unshared applications executing within a terminal server environment to interact with clients of a terminal server, comprising:
sharing a first application with a client of a server, wherein said sharing
5 comprises executing the first application on the server and routing by the terminal server of input/output for the first application to the client;
executing a second application on the server, said second application being unshared and without routing by the terminal server of input/output for the second application to the client;
10 determining, by the second application, a session identifier for the client corresponding to said sharing of the first application; and
using the session identifier to send a message to the client.
2. The method of claim 1, wherein the first application is unaware it is
15 being shared.
3. The method of claim 1, further comprising:
using the session identifier to establishing an input/output communication
20 channel with the client.
4. The method of claim 3, further comprising:
receiving over said communication channel a response to the message.
5. The method of claim 3, further comprising:
25 monitoring, by the second application, of accessing of resources by the first application; and
determining, by the second application, an error condition arising from
accessing a particular resource by the first application;
wherein the message concerns the error condition and the message is
30 sent to the client over said communication channel.

17

6. The method of claim 5, wherein the second application is a virus scanner, and wherein the error condition is a virus detected in the particular resource.

7. The method of claim 1, further comprising:
5 monitoring, by the second application, of accessing of resources by the first application; and
determining, by the second application, an error condition arising from accessing a particular resource by the first application;
wherein the message concerns the error condition.

10 8. The method of claim 7, wherein the second application is a virus scanner, and wherein the error condition is a virus detected in the particular resource.

9. The method of claim 7, further comprising:
15 starting an elapsed-time counter; and
starting scanning the particular resource for viruses;
wherein said determining the error condition comprises identifying the elapsed-time counter has exceeded a scanning time-limit.

20 10. The method of claim 7, further comprising:
starting scanning the particular resource for viruses; and
determining if the particular resource corresponds to an archive file, and if so, starting an elapsed-time counter before scanning the archive file for viruses;
wherein said determining the error condition includes determining if the
25 elapsed-time counter exceeded a scanning time-limit.

Sub
a2
30 11. A readable medium having encoded thereon instructions for allowing unshared applications executing within a terminal server environment to interact with clients of a terminal server, said instructions when executed capable of directing a processor to:

share a first application with a client of a server, wherein said sharing comprises executing the first application on the server and routing by the terminal server of input/output for the first application to the client;

execute a second application on the server, said second application being unshared and without routing by the terminal server of input/output for the second application to the client;

determine, by the second application, a session identifier for the client corresponding to said sharing of the first application; and

use the session identifier to send a message to the client.

12. The medium of claim 1, said instructions comprising further instructions to direct the processor to:

use the session identifier to establish an input/output communication channel with the client.

13. The medium of claim 12, said instructions comprising further instructions to direct the processor to:

receive, over said communication channel, a response to the message.

14. The medium of claim 12, said instructions comprising further instructions to direct the processor to:

monitor, by the second application, accessing of resources by the first application;

determine, by the second application, an error condition arising from accessing a particular resource by the first application;

configure the message to include the error condition; and
send the message over said communication channel.

15. The medium of claim 14, wherein the second application is a virus scanner, and wherein the error condition is a virus detected in the particular resource.

16. The medium of claim 11, said instructions comprising further instructions to direct the processor to:

monitor, by the second application, of accessing of resources by the first application; and

5 configure the message to include the error condition; and
send the message over said communication channel.

17. The medium of claim 16, wherein the second application is a virus scanner, and wherein the error condition is a virus detected in the particular resource.

10

18. The medium of claim 16, said instructions comprising further instructions to direct the processor to:

start an elapsed-time counter; and

start scanning the particular resource for viruses;

15 wherein said instructions for determining the error condition further
comprise instructions for determining that the elapsed-time counter has exceeded a
scanning time-limit.

19. The medium of claim 16, said instructions comprising further instructions to direct the processor to:

start scanning the particular resource for viruses; and

determine if the particular resource corresponds to an archive file, and if
so, starting an elapsed-time counter before scanning the archive file for viruses;

20 wherein said instructions for determining the error condition further
25 comprise instructions for determining that the elapsed-time counter has exceeded a
scanning time-limit.

Sub
Q3 20. A system for unshared applications executing within a terminal
server environment to interact with clients of a terminal server, comprising:

a sharing arrangement for sharing a first application with a client of a server, wherein said sharing comprises executing the first application on the server and routing by the terminal server of input/output for the first application to the client;

a file access monitor for monitoring file accesses by the first application;

5 a virus scanning arrangement executing on the server for scanning accessed files for viruses;

a timer arrangement for timing said scanning accessed files for viruses;

10 a scan-termination arrangement for interrupting the virus scanning arrangement if said scanning accessed files for viruses does not complete within a timeout period;

means for determining, by the second application, a session identifier for the client corresponding to said sharing of the first application; and

means for sending a message, to the client according to the session identifier, indicating said scanning accessed files for viruses timed out.